



WIRELESS POS Terminal

4G
MODEL: AF 70

دستگاه کارتخوان مدل AF70 نسل جدید

از پایانه‌های فروشگاه‌ها با طراحی زیبا و وزن کم است که امنیت بالایی را برای هر تجربه پرداخت فراهم می‌کند.

دستگاه کارتخوان مدل AF70 امکانات کامل ارتباطی و امنیتی را همزمان ارائه می‌کند و می‌تواند نیازهای روزانه را در تمام محیط‌های پویا و کسب و کارهای مختلف برطرف کند.

قابلیت‌های دستگاه

- پشتیبانی از کارت‌های نوار مغناطیسی و کارت‌های ای‌سی غیر تماسی
- قابلیت NFC و پشتیبانی از شبکه پرداخت APPLE PAY
- ظرفیت بالای باتری
- توان مصرفی بهینه جهت افزایش طول عمر باتری
- اسکن یک بعدی و دو بعدی (QR CODE)
- پشتیبانی از شبکه ارتباطی 2G و 4G
- قابلیت اتصال به WIFI جهت تراکنش بدون نیاز به سیم کارت
- پشتیبانی از فن آوری Bluetooth





Specifications

Processor

Main cpu: ARM Cortex-R5 , maximum clock
Frequency 800 MHz
Security CPU: 32bit, ARM cortex - m0, maximum
Clock frequency 96 MHz

Memory

Main CPU: 16 MB Flash, 8 MB RAM
Secure CPU: 512 KB Flash, 64 KB RAM

Display

2.4 "(320*240)TFT

RTC

Built in RTC to save the clock; Button
Battery life > 5 years

Key

19 physical keys: 1 power key, 12 digit / letter
Keys and 6 function keys, cancel, clear, F1/F2 , menu



Contact IC card

Comply with ISO 7816 and China financial
Integrated circuit (IC) card specification;
The card holder can be used for more than
300000 times

Contactless card

13.56 MHz;
Support iso 14443 type A & B standard;
Qpboc compliant

Magnetic stripe card

Support two track data reading;
It supports two-way card swiping. The swiping
Speed ranges from 10 cm / s to 100 cm/s.
The service life of the magnetic stripe reader can
reach more than 400000 times;
It conforms to iso 7811 and iso 7812 standards

Camera

Support bar code, two-dimensional code Scanning

Printer

High speed thermal printing, printing life
is not less than 50Km
the specification is 58mm in width and
40mm in diameter

WIFI

802.11 a/b/g/n, 2.4G

Bluetooth

BLE 4.0 and above

Mobile communication

South American version
FDD-LTE: B1/B3/B5/B7/B8/B28-A/B28-B;
TDD-LTE: B40
GSM: B2/B3/B5/B8
European Version
FDD-LTE: B1/B3/B5/B7/B8/B20;
FDD-LTE: B38/B40/B41
GSM: B3/B8



SIM/SAM Slot

1 SIM + 2 SAMs | 2SIMs + 1 SAM

External interface

1TYPE-C USB

Battery

3.7V, 2600mAh

Buzzer

Support

Indicator light

1 power indicator + 4contactless indicator

Certificate

PBOC3.0L1&L2
EMV L1&L2 , EMV CL L1
PCI PTS 5.X, SRED
UPTS2.0 Security assessment of UnionPay
terminal
Mastercard paypass, visa PayWave,
Discover D-PAS, American ExpressPay
SRRRC/CTA/TQM/3C/CE/BIS/WPC